

TECHNICAL DATASHEET

Filaticum PLA ESD

3D printing filament for FDM/FFF printer

Product Description

This filament is used mainly in the electronics industry, where electrostatic charging of a printed object can cause problem. Objects printed with Filaticum ESD does not charge electrostatically due to the special additives. Filaticum ESD provides surface resistance at megaohm order of magnitude, but this highly depends on the size and shape of the printed object.

Applications

Boxes, containers, covers which protect the products manufactured in the electronics industry. Covers of products used in electrical environment. ESD safe fixtures and parts. Covers and boxes of electronic devices.

Specification

Code	PLAESD010, PLAESD011
Diameter	1,75 mm, 2,85 mm
Tolerance	+-0,05 mm, +-0,1 mm
Colour	black
Weight	0,75 kg, 2,5 kg
Filament length	ca.: 250 m/0,75 kg

Printer Settings

Nozzle temperature	195-250 °C
Nozzle size	0.4-1,2 mm
Bad temperature	max 70 °C
Bad condition	capton, glass, tape or glue
Cooling fun	recommended up 100%
Layer height	0,4-0,8 mm
Print speed	20-80 mm/s, optimal, max 250 mm/s

These printer settings are recommended for the start, they could be modified according to the printer, the printed objects and the required mechanical parameters.

Raw Material Properties


Physical properties *	Method	PLA
Specific Gravity, g/cm³	D792	1.24
Heat Distortion Temp (HDT)*,°C	D790	55
Glass Trans. Temp, °C	D3418	55-60
Tensile Strength, MPa	ISO 527	60
Tensile Elongation, %	ISO 527	6,00
Tensile Modulus, MPa	ISO 527	3800
Notched Izod Impact, kJ/m2	ISO 180	16

^{*}Typical properties for injection molded amorphous bars; not to be construed as specifications.

^{**66} psi (0.45 MPa)



Mechanical Properties of 3D Printed Specimen



Properties		Test method
Tensile Strength	under testing	ISO 527
Tensile Modulus	under testing	ISO 527
Tensile Elongation	under testing	ISO 527
Notched Izod Impact	under testing	ISO 180

Material Safety

RoHS compliance	yes
REACH compliance	yes

Producer

Filamania Ltd., 2310 Szigetszentmiklós, Fenyőfa utca 23/a, Hungary tel: + 36 30 9313 973, email: info@filaticum.com, www.filaticum.com

Disclaimer: The information presented are typical values intended for reference and comparison purposes only. They should not be used for design specifications or quality control purposes. End-use material performance can be impacted by, but not limited to part design, end-use conditions, test conditions, etc. Actual values will vary with build conditions. Product specifications are subject to change without notice. The performance characteristics of these materials may vary according to application, operating conditions, or end-use. Each user is responsible for determining that the material is safe, lawful and technically suitable for the intended application, as well as for identifying the proper disposal method consistent with applicable environmental laws and regulations. Filamania Ltd. makes no warranties of any kind, express or implied including but not limited to the warranties of merchantability, fitness for a particular use.